



High Pressure

Four High Tensile Spiral Hose meets or exceeds EN 856 4SP ISO 1307

VINCKE HH-09

EN856 4SP											
Code	Nominal \varnothing	Inside \varnothing	Braid \varnothing	Outside \varnothing	Max. Working Pressure	Burst Pressure	Minimum Bend Radius	Weight			
Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m	
0904	04	1/4"	6,4	14,6	17,6	450	6525	1800	26100	150	565
0906	06	3/8"	9,5	17,5	21,2	445	6453	1780	25810	180	730
0908	08	1/2"	12,7	20,3	24,4	415	6018	1660	24070	230	865
0910	10	5/8"	16	23,8	28	350	5075	1400	20300	250	1035
0912	12	3/4"	19	28,2	32	350	5075	1400	20300	300	1485
0916	16	1"	25,4	35,1	39,1	280	4060	1120	16240	340	1900

Construction:

Tube: seamless oil resistant synthetic rubber

Reinforcement: 4 high tensile steel spiral

Wrapped cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C discontinuous)

